

# Peachtree Tipper

C O M P A N Y



*Simplified design for ease of maintenance*



*3" Bore Cylinder with 1-1/2" Nitrided Rod with Cross Tube*

## *Introducing the Peachtree Tipper Model PT-4*

- *Durable construction*
- *Simplified design for ease of maintenance*
- *3" bore cylinder with 1-1/2" Nitrided rod*
- *Break-away feature to minimize damage when properly mounted*
- *ANSI Z245.60-2008 Type B Containers (domestic 2-bar carts)*

*WasteEquipmentParts.com  
PO Box 10  
Toccoa, Georgia 30577*

*Phone: 1-800-763-3810*

*Fax: 1-866-397-1438*

*Email:  
info@WasteEquipmentParts.com*

# LIFT UNIT SPECIFICATIONS:

## MOUNTING BRACKET:

- Unit is bolted to mounting bracket for ease replacement

## HYDRAULIC CYLINDER:

- 3,000 PSI Working Pressure
- Cross Tube Mounting Both Ends for Ease Replacement of the cylinder
  - 1-1/2 Nitrided Piston Rod
- Pressure tested to 1.5 times the normal working pressure to insure performance reliability
  - 3" Bore with Recessed ORB ports

## CART LIFTING CAPABILITY:

- ANSI Type B (American 2 bar cart)

## Major Pivot Points:

- All major pivot points are equipped with cast bronze
  - Bushings and "Zerk" type grease fittings

## IMPACT RELEASE DEVICE:

Mechanical kick out feature that allows the unit to release from the Vertical (down) position when struck by the street surface while the truck is in Forward motion

## LIFT BAR POCKET:

- The lift bar pocket (saddle) is designed to minimize cart free movement when unit is in the up position. Bolted on for ease of replacement if damaged.

## CART LIFTING CAPACITY:

- Will lift a minimum of 550 pounds at 1800 PSI hydraulic pressure.



*All Bronze Bushings with Grease Points*

  
C O M P A N Y